



Running Contract Details	
Equipment Name	Microtome
Running Contract Valid Till	15-05-2021
Tender Ref No	KMSCL/EP/T319/626B/2019(R)
Tendered Quantity	20
Supplier Name	M/s Radical Scientific Equipments Pvt Ltd
GST No	06AACCR8985N1ZI
Installation & Delivery Period	8 Week(s)
Up-time / PM vist	95% & 2 Visits per year
Warranty period	2 Years

Supplier`s Details		
Address	Contact Details	
9th Milestone Ambala-Jagadhri Road Khudda Kalan Ambala Cantt-133104 (Haryana)	Contact Person	Mr. Vikram Singh Chauhan
	Phone	
	Mobile No	89030997827
	Email	tenders@radicalscientific.com

Item-wise Price Details				
#	Item Details	Unit Rate (Incl.all taxes & charges)	Service Charges (Through KMSCL)	Grand Total
1	Microtome <i>Model & Make : RMT-30A / Radical</i>	85668 Incl.GST :18%	5996.76	91664.76
2	Rate of one Dipoable blade	200.6 Incl.GST :18%	14.04	214.64
		85868.6	6010.8	91879.4

Annual / Comprehensive Maintenance Charges (Exl.Tax)				
Rate	3 rd Year	4 th Year	5 th Year	
Microtome				
Labour	1,090.00	1,090.00		1,090.00
Comprehensi ve	1,450.00	1,450.00		1,450.00

Other terms & conditions

1. The supplier shall execute an agreement with the purchaser as per tender conditions (agreement format is given in the tender document).
2. The supplier shall submit performance security amounting to 5% of the value of the supply order.
3. The labour & comprehensive charges of equipment after the completion of warranty period is finalized by KMSCL as mentioned above.
4. Since discount rate is not applicable for equipment under Running Contract of KMSCL, purchase/supply order can be issued directly to supplier at the given rate with tax & other charges (exclusive of KMSCL service charges).
5. If purchase/supply order is issued directly to the supplier, KMSCL service charge need not be paid. But the copy of the said order may be forwarded to KMSCL for information.

Technical Specification

Equipment :Microtome

1. Coarse feed wheel-80mm.
2. Adjustable hand wheel system.
3. Hand wheel allowed to locked in any position.
4. Precise sectioning of tissues up to 1 micron thickness.
5. The feed indicator, located in front of microtome for accurate feed selling from 1-50 microns.
6. Should have precision orientation system.
7. Should be supplied 5 nos of disposable blade along with the machine